



EGT ENCORE Encoder

Specifications

VIDEO

Input	Analog composite Serial Digital (SDI)
SNR (un-weighted)	>52dBrms
Aspect Ratio	4:3, 16:9
Vertical Resolution	480 (NTSC) and 576 PAL
Horizontal Resolution	720, 704, 640, 544, 528, 480, 352
Encoding Type	MPEG-2 MP@ML (4:2:0)
Rate	1.5 – 15.0 Mbps (CBR), 0.3 – 15.0 Mbps (VBR)
GOP structure	Variable or fixed GOP Automatic I-frame insertion
Pre-filtering	Adaptive temporal-spatial noise filtering Motion adaptive temporal filter Motion compensated temporal filter

AUDIO

Input	Analog (balanced/unbalanced) Digital (AES/EBU, SDI) DTMF and GPI (DPI Cue-trigger)
Channels	Up to 4 stereo pair per video
Level Adjustment	-7.0 to 24.0 in 0.5dB steps
Operating Modes	Single channel mono Dual channel mono Stereo, Joint Stereo
Encoding Type and Rate	MPEG Layer II: 64 – 384 Kbps AC-3: 56 – 640 Kbps
Sample Frequencies	32 kHz, 44.1 kHz, 48 kHz

EGT ENCORE Encoder Technical Specification

Specifications Continued

SERVICES

Output	Single Program ASI Multi program ASI (Cascade) Ethernet (10/100 Base T)
System Management	HTTP browser SNMP ORCHESTRA Element Manager
VBI	Closed Caption, XDS, V-CHIP WSS VPS WST teletext SCTE 127 Gemstar TV Guide SCTE 127 AMOL I/II
DPI	SCTE 35, SCTE 104 (DVS525 R.3)

PHYSICAL

Dimensions	1.75"H x 19"W x 11.78"D (4.45cm x 48.26cm x 29.94cm)
Weight	14lbs/6.4Kg (4 channel unit)
Capacity	4 channels per rack unit
Input Voltage Range	100-240V ~3A Optional – 48V DC supply
Line Frequency	47-63 Hz
Typical Consumption	38 W per channel
Environment Cooling	4 fans; airflows side to side
Operating temp	32 to 122 F, 0 to 50 C
EMC/compliance	FCC part 15 Class A CE, UL, cUL

Specifications are subject to change without notice.

The capabilities, system requirements and/or compatibility with third-party products described herein are subject to change without notice. ARRIS, the ARRIS logo, Auspice®, C3™, C4®, C4c™, Cadant®, C-COR®, CHP Max®, ConvergeMedia™, Cornerstone®, CXM™, D5™, Digicon®, Flex Max®, Keystone™, MONARCH®, n5™, nABLE™, NSM™, nVision®, OpsLogic®, OpsLogic Service Visibility Portal™, PLEXIS®, PowerSense™, Regal®, ServAssure™, Service Visibility Portal™, TeleWire Supply®, TLX®, Touchstone®, VoiceAssure™, VSM™, and WorkAssure™ are all trademarks of ARRIS Group, Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and the names of their products. ARRIS disclaims proprietary interest in the marks and names of others. © Copyright 2009 ARRIS Group, Inc. All rights reserved. Reproduction in any manner whatsoever without the express written permission of ARRIS Group, Inc. is strictly forbidden. For more information, contact ARRIS.



www.arrisi.com