



EGT VIPr2600 Video Transcoder

Specifications

VIDEO

Input	MPEG-2 HD MP@HL over IP MPEG-2 SD MP@ML over IP
# of Channels	1-8 HD channels 1-42 SD channels
Output	MPEG-2 HD MP@HL, MPEG-2 SD MP@ML
Chroma Format	4:2:0
Resolutions	up to 1920x1080i, 1280x720p, 720x480i
Frame Rates	29.97 fps interlaced, 59.94 fps progressive
Encoded Bit Rates	1-20 Mbps
Bit Rates Modes	CBR or Closed-loop VBR
Aspect Ratio	16:9, 4:3
Processing	Integrated decode-recode and stat mux Adaptive reuse of original coding parameters Film mode 3:2 pull-down detection

ENVIRONMENTAL

Operating Temperature Range	0°C to 40°C
Humidity	5-95%; non-condensing
Power Consumption	Watts: 250W per node
Power Supply Input	Volts: 100-240 Vac Frequency: 47-63 Hz Amperes: ~2.3 Amps per node
Form Factor	1RU
Dimensions	19.0" x 1.75" x 24" (WxHxD)
EMC/Safety Compliance	FCC part 15 Class A, CE, UL, ULc

AUDIO

Input Audio Formats	Dolby Digital (AC-3), 5.1, MPEG-1 Layer 2
Operating Modes	Stereo, Single Channel Mono, Dual Channel Mono, Joint Stereo
Encoding	Passthrough

EGT VIPr2600 Technical Specification

Specifications Continued

SERVICES

Closed loop encoding	3+HD channels into 256 QAM 15+ SD channels into a 256 QAM
DPI	SCTE-35 Passthrough
VBI Services	Captions Passthrough of line 21 and EIA708 advanced captions, Data Passthrough of SCTE127 data services
EAS	Passthrough

IP PORTS

Media Interfaces	Dual Gigabit
Rate	10/100/1000 Base T (Auto Negotiate)
Duplex	Full Duplex (Auto Negotiate)
Type	Unicast or Multicast
Format	MPEG-2 MPTS over UDP
Management Interface	10/100 Base T (Auto Negotiate)
Connector Types	RJ45

CONFIGURATION

User Interface	GUI
Monitor and Control	SNMP
Redundancy	Fully redundant chassis support
Hot Swappable	Fans
Removable	Power supply, Fan trays

Contact Customer Care for sales and product information via the ARRIS website (www.arris.com) or as indicated below:

United States: 866-36-ARRIS

International: +1-678-473-5656

Specifications are subject to change without notice.

The capabilities, system requirements and/or compatibility with third-party products described herein are subject to change without notice. ARRIS, the ARRIS logo, Auspice®, C3™, C4®, C4c™, Cadant®, C-COR®, CHP Max®, ConvergeMedia™, Cornerstone®, CXM™, D5™, Digicon®, Flex Max®, Keystone™, MONARCH®, n5™, nABLE™, NSM™, nVision®, OpsLogic®, OpsLogic Service Visibility Portal™, PLEXIS®, PowerSense™, Regal®, ServAssure™, Service Visibility Portal™, TeleWire Supply®, TLX®, Touchstone®, VoiceAssure™, VSM™, and WorkAssure™ are all trademarks of ARRIS Group, Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and the names of their products. ARRIS disclaims proprietary interest in the marks and names of others. © Copyright 2009 ARRIS Group, Inc. All rights reserved. Reproduction in any manner whatsoever without the express written permission of ARRIS Group, Inc. is strictly forbidden. For more information, contact ARRIS.



www.arris.com