



XMS Mini: ConvergeMedia™ Distribution Platform Technical Specifications

XMS Mini Server Specifications

Power

Power – Streaming	250W 110VAC / 250W 220VAC (TYPICAL)
Input Voltage	100 – 240VAC
Frequency	60-50Hz
Power Source Phasing	Single-Phase AC

Dimensions

Height	3.5 inches / 89 mm (2RU)
Width	17.2 inches / 437 mm
Depth	25.5 inches / 648 mm
Weight	45 lbs / 20.4 Kg (with drives)

Performance

Streaming	2 Gbps
Content store	4 TB/6TB

Interfaces

Streaming	Multiple 1 Gbps (Copper)
Management	2 Gigabit Ethernet ports
Stream/Session Management	RTSP

Redundancy

Streaming Interface	Interface Failover
Power Supply	Dual redundant hot swap
Fans	Dual redundant hot swap

Streaming Server Environmental

Operating Temperature	10 to 35° C (50 to 95° F)
Storage Temperature	-40 to 70° C (-40 to 158° F)
Operating Humidity	8% to 90% non-condensing
Storage Humidity	5% to 95% non-condensing

ARRIS Technical Specifications

Regulatory & Safety Compliance

EMC FCC pt15 Class A
Safety EN/IEC/UL60950-1, EN55022, EN55024,
CB Report: FCC/CE, CSA, TUV-GS, RoHS

Management System Interfaces

Content Transfer FSI

Specifications are subject to change without notice.

Page 2 of 2

The capabilities, system requirements and/or compatibility with third-party products described herein are subject to change without notice. ARRIS, the ARRIS logo, Auspice®, C3™, C4®, C4c™, Cadant®, C-COR®, CHP Max®, ConvergeMedia™, Cornerstone®, CXM™, D5™, Digicon®, Flex Max®, Keystone™, MONARCH®, n5™, nABLE™, NSM™, nVision®, OpsLogic®, OpsLogic Service Visibility Portal™, PLEXiS®, PowerSense™, Regal®, ServAssure™, Service Visibility Portal™, TeleWire Supply®, TLX®, Touchstone®, VoiceAssure™, VSM™, and WorkAssure™ are all trademarks of ARRIS Group, Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and the names of their products. ARRIS disclaims proprietary interest in the marks and names of others. © Copyright 2009 ARRIS Group, Inc. All rights reserved. Reproduction in any manner whatsoever without the express written permission of ARRIS Group, Inc. is strictly forbidden.
For more information, contact ARRIS.