



Ruckus Wireless® ZoneFlex™ 7962

Dualband 802.11n Smart Wi-Fi® Access Point

Benefits

- Highest performance at range
- Extended coverage means fewer APs
- Wire-like reliability
- Concurrent support for high-definition IP video, voice
- Automated deployment keeps things ultra simple
- Distributed forwarding architecture eliminates
- Simple extension of WLAN services
- Investment protection for legacy Wi-Fi networks
- Hassle free migration to higher speed Wi-Fi
- Enables new class of provider hotspots services



The Ruckus ZoneFlex 7962, the industry's top performing dual-band 802.11n access point with adaptive antenna technology, delivers ultra-high speed, reliable and longest-range connectivity within challenging RF environments.

The ZoneFlex 7962 is based on adaptive antenna technology that extends signal range two to four times while minimizing packet loss by constantly routing Wi-Fi transmissions over the highest performing signal paths.

The world's only enterprise-class AP that concurrently supports Automatic Interference Mitigation (AIM), spatial multiplexing and adaptive antenna technology, the ZoneFlex 7962 delivers the industry's most solid 802.11n performance at range. Because the ZoneFlex 7962 is able to constantly find the best RF paths for each packet, once deployed, enterprises never have to worry about constant site surveys as the environment changes.

It's also the only 802.11n product purpose-built for hotels, schools and enterprises that enables high-definition IPTV, video-on-demand and other video applications while supporting VoIP and data applications for guests and employees.

Ideal for multimedia and high-density user environments, the ZoneFlex 7962 can be deployed as a standalone access point or as part of centrally-controlled Smart Wireless LAN with the Ruckus ZoneDirector. Smart Mesh Networking, another unique feature, makes the ZoneFlex 7962 perfect for reliably extending wireless LAN services to areas where cabling Ethernet isn't possible or economical—saving time and money. With dual radios, the ZoneFlex 7962 delivers high-performance throughout the mesh network.

The ZoneFlex 7962 is also perfect for service providers interested in delivering high-performance multimedia hotspots, hotzones and managed services. Coupled with the Ruckus FlexMaster Wi-Fi management platform, the ZoneFlex 7962 opens the door for extending branded broadband services and new revenue-generating services.

Automated deployment keeps configuration and installation super simple—even for large enterprise deployments. And support for standard 802.3af Power Over Ethernet (PoE) eliminates migration pains by leveraging existing PoE switches.

Benefits

Highest performance at range

Adaptive antenna technology enables Wi-Fi signals to be constantly formed and directed over the best performing signal paths thereby ensuring the lowest packet loss and highest performance at range.

Extended coverage means fewer APs

Directional, high-gain antennas dynamically combine to give hotspot operators and enterprises 2- to 4-times the coverage over typical consumer and enterprise APs.

Wire-like reliability

Advanced smart antenna array and Quality of Service (QoS) technology combine to deliver the industry's most reliable and highest performing 802.11n system available.

Concurrent support for high-definition IP video, voice and data

A directional, high-gain antenna finds the best path for any given transmission allowing unprecedented support for picture perfect high-definition video, crystal clear voice and high speed data.

Automated deployment keeps things ultra simple

Configuration and ongoing management is radically simplified through a Web-based wizard and automated deployment capabilities

Distributed forwarding architecture eliminates bottlenecks

Standalone or controller-based, traffic is not forced through the controller eliminating any single point of failure or performance bottleneck.

Simple extension of WLAN services

Integrated support for Smart Mesh Networking gives enterprise the power to easily extend WLAN services wherever needed and without having to run costly and cumbersome Ethernet cabling to every AP.

Investment protection for legacy Wi-Fi networks

The ZoneFlex 7962 gives enterprises protection over their wireless investments by enhancing performance and range for legacy 802.11a/b/g clients.

Hassle free migration to higher speed Wi-Fi

Support for standard 802.3af power over Ethernet allows enterprises to use existing PoE switches without costly upgrades.

Enables new class of provider hotspots services

New revenue opportunities for operators such as Voice-over-WLAN services, extended enterprise access and IP video applications.



Patented BeamFlex™ Technology Extends Signal Range, Improves Stability of Client Connections

The ZoneFlex 7962 Smart Wi-Fi access point integrates a software-controlled smart antenna array that delivers 7dBm of signal gain and 15dB of interference rejection. This allows a 2 to 4x improvement in signal range and a reduction in packet loss from the ability to automatically avoid interference and obstacles.

Advanced WLAN Applications with Smart/OS

When used with the Ruckus ZoneDirector Smart WLAN controller, the ZoneFlex 7962 supports a wide range of value-added applications such as guest networking, Smart Wireless Meshing, Dynamic PSK, hotspot authentication, wireless intrusion detection and many more. With Smart/OS, up to 32 discrete WLANs can be created and mapped to the same or different APs or VLANs. WLANs can also be grouped and shared by specific APs. In a centrally managed configuration, the ZoneFlex 7962 works with a wide range of authentication servers including Microsoft's Active Directory, LDAP, and RADIUS.

Flexible Deployment Options

ZoneFlex 7962 APs can be deployed in as a standalone AP or as part of a centrally managed wireless LAN using ZoneDirector Smart WLAN controllers. ZoneFlex 7962's can be deployed across any L2/L3 network and/or meshed without Ethernet cabling. When used with the ZoneDirector, the ZoneFlex 7962 is automatically configured through the network making deployment quick and easy.

Complete Local and Remote Management


The ZoneFlex 7962 can be managed as a standalone AP through a Web-based GUI, using SNMP or through the Ruckus FlexMaster Wi-Fi remote management system. Local management can also be performed using the ZoneDirector Smart WLAN controller. FlexMaster is a LINUX-based software platform that uses industry-standard protocols to perform bulk configuration, fault detection, monitoring and a wide range of troubleshooting capabilities over a wire area connection. The ZoneDirector enables local management and control of APs, adding value-added services such as transmit power and channel management, guest networking and meshing.



Features

- Concurrent dual-band (5GHz/2.4GHz) support
- Adaptive antenna technology and advanced RF management
- Up to 7dBi signal gain / -15dB interference rejection
- Automatic interference avoidance, optimized for high-density environments
- Integrated smart antenna array with over 4,000 unique patterns for ultra reliability
- Standard 802.3af Power over Ethernet (PoE)
- 2 to 4 times extended range and coverage
- Multicast IP video streaming support
- 600 Mbps of user throughput (300 Mbps/radio)
- Four queues per client station
- 16 BSSIDs with unique QoS and security policies
- WEP, WPA-PSK (AES), 802.1X support for RADIUS and Active Directory*
- Smart Mesh Networking*
- Zero-IT and Dynamic PSK*
- Admission control/load balancing*
- Band steering and airtime fairness
- Captive portal and guest accounts *
- Wall or ceiling mountable


* When used with Ruckus ZoneDirector controller.



Horizontally and vertically polarized antenna elements provide over 4000 potential antenna combinations for high availability Wi-Fi


An automatic signal optimizer modifies RF transmissions based on the orientation of the access point

A patented smart antenna array integrates high-gain, directional antenna elements deliver up to 7dBi in signal gain and up to -15dB of interference avoidance for unprecedented range extension, signal reliability and higher data rates.



ULTRA HIGH PERFORMANCE WLANS

Through the use of an integrated smart antenna array specifically designed for 802.11n networking, the Ruckus ZoneFlex 7962 provides the industry's highest performing enterprise WLAN solution. WLANs can be easily extended where Ethernet is unavailable through the use of Smart Mesh Networking.



CONCURRENT IP VIDEO AND DATA

With integrated quality of service mechanisms and an intelligent multi-element antenna array, the ZoneFlex 7962 stands alone as the only dual-band 802.11n system capable of supporting picture perfect transmission of IP-based streaming video concurrently with high-performance data traffic.

Specifications

Physical Characteristics	
Power	External power adapter Input: 110-240V AC Output: 12V DC, 1.5A Power over Ethernet Class 0
Physical Size	19.43cm (L), 14.43cm (W), 12.38cm (H)
Weight	680 grams (1.5 lbs.)
Antenna	Internal software-configurable antenna array with directional and omni high-gain elements that provide over 4,000 unique antenna patterns
Ethernet Ports	2 ports, auto MDX, auto-sensing 10/100/1000 Mbps, RJ-45 Power over Ethernet (802.3af)
Lock Option	Integrated Kensington lock
Environmental Conditions	Operating Temperature: 32°F (0°C) to 122°F (50°C) Operating Humidity: 15% to 95% non-condensing
Power Draw	12.95W (PoE) 15W (12V DC)
Performance and Supported Configurations	
Concurrent Stations	Up to 200
Target UDP Throughput	150-200 Mbps (300 Mbps bursts) sustainable throughput for a 5000 sq. foot (460 sq meter) area for each radio for each band
Vo-Fi Clients	Up to 20 simultaneously
Traffic Management and Quality of Service	
Classes of Service	Voice, video, best effort and background
Software Queues	Four per station
802.11e	Supported
Automatic Traffic Classification	Automatic type of service tagging for multicast video packets
Rate Limiting	Supported
VLAN Support	802.1Q
Heuristic Classification	Supported
Deployment	
Options	Managed by ZoneDirector Individually managed Managed by FlexMaster
Management	
Configuration	Web user interface, CLI (Telnet), SSH HTTP/S, SNMP via ZoneDirector, TR-069 via FlexMaster
Statistics	LAN, wireless and associated stations (accessible via Web UI)
Auto AP Software Updates	FTP or TFTP, remote auto available
Wi-Fi*	
Standards	IEEE 802.11a/b/g/n 2.4 GHz and 5 GHz concurrent operation
Supported Data Rates	802.11n: 6.5Mbps to 144.4Mbps (20MHz) 6.5Mbps to 300Mbps (40MHz) 802.11a: 54, 48, 36, 24, 18, 12, 9 and 6 Mbps 802.11b: 11, 5.5, 2 and 1 Mbps 802.11g: 54, 48, 36, 24, 18, 12, 9 and 6 Mbps
Radio Chains	3 x 3
Spatial Streams	2
RF Power Output	28 dBm/600 mW
Channelization	20 MHz and/or 40 MHz
Frequency Band	IEEE 802.11n: 2.4 – 2.484 GHz and 5.15 – 5.85 GHz IEEE 802.11a: 5.15 – 5.85 GHz IEEE 802.11b: 2.4 – 2.484 GHz
Operating Channels	US/Canada: 1-11, Europe (ETSI X30): 1-13, Japan X41: 1-13 5GHz channels: Country dependent for the following channel ranges: 36, 40, 44, 48, 52, 56, 60, 64, 100, 104, 108, 112, 116, 120, 124, 128, 132, 136, 140, 149, 153, 157, 161, 165
BSSID	Up to eight per radio 9 (16 total)
Power Save	Supported
Wireless Security	WEP, WPA-PSK, WPA-TKIP, WPA2 AES, 802.11i Authentication via 802.1X, local authentication database, support or RADIUS, LDAP, and ActiveDirectory
Certifications	<ul style="list-style-type: none">• U.S., Europe, Australia, Canada, China, Colombia, Hong Kong, India, Malaysia, Mexico, New Zealand, Philippines, Singapore, Taiwan, Thailand, Vietnam• WEEE/RoHS compliance• EN 60601-1-2• Wi-Fi Alliance Certification

Ruckus Wireless® ZoneFlex™ 7962

Ordering Information

ARRIS #	Mfg #	Description
TBD	TBD	Centrally managed concurrent dual band 802.11n access point
Optional Accessories		
TBD	TBD	Flat ceiling & wall mounting kit
TBD	TBD	Drop ceiling mounting kit
TBD	TBD	PoE injector (sold in quantities of 10 or 100)
794015	SVC-CTRCT	1 Year Service Contract Required.

PLEASE NOTE: When ordering you must specify the destination region by indicating -US, -EU, -UK, -UN, -AU, -UU or -IN instead of XX.

BeamFlex, ZoneFlex, MediaFlex, MetroFlex, FlexMaster, ZoneDirector, SpeedFlex, SmartCast, and Dynamic PSK are trademarks of Ruckus Wireless, Inc.

The capabilities, system requirements and/or compatibility with third-party products described herein are subject to change without notice. ARRIS, the ARRIS logo, Auspice®, C3™, C4®, C4c™, Cadant®, C-COR®, CHP Max5000®, ConvergeMedia™, Cornerstone®, CORWave™, CXM™, DS®, Digicon®, ENCORE®, Flex Max®, HEMJ®, Keystone™, MONARCH®, MOXI®, n5®, nABLE®, nVision®, OpsLogic®, OpsLogic® Service Visibility Portal™, PLEXIS®, PowerSense™, QUARTET®, Regal®, ServAssure™, Service Visibility Portal™, TeleWire Supply®, TLX®, Touchstone®, VIPr™, VSM™, and WorkAssure™ are all trademarks of ARRIS Group, Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and the names of their products. ARRIS disclaims proprietary interest in the marks and names of others. © Copyright 2011 ARRIS Group, Inc. All rights reserved. Reproduction in any manner whatsoever without the express written permission of ARRIS Group, Inc. is strictly forbidden. For more information, contact ARRIS.



www.arrisi.com